

# Linear dynamical system identification

... basic elements and Labs guidelines

Charles Pousot-Vassal

February 20, 2026



# Introduction

## Course plan, overview and questions addressed

### L1: Overview, signals construction, pre-treatment and non-parametric analysis

- ▶ Realization, transfer functions, ...
- ▶ Construct an experimental plan and signals.
- ▶ How to analyze signals, and derive some properties?

### L2: Data-driven model construction in the time- and frequency-domain

- ▶ Construct a linear model from time- or frequency-domain data.
- ▶ How much is it valid? How to validate, discuss, amend it?

### L3: L2 cont'd & Labs guidelines

- ▶ Illustration in practice
- ▶ Experimental setup & numerical tools presentation.
- ▶ Methodology for the lab.

### L3: L2 cont'd & Labs guidelines

- ▶ Experimental setup & numerical tools presentation.
- ▶ Methodology for the lab.

### Notions treated

- ▶ A detailed illustration of L1-L2
- ▶ Presentation of the experimental test benches
- ▶ Talk and learn from user (setup, measurements, inputs, disturbances, knowledge, stability, etc.)
- ▶ Getting started and method (code, report, organisation, etc.)
- ▶ Group evaluation

# Content

Introduction

**A detailed identification example #1**

A detailed identification example #2

Experimental setup



Working methodology

Evaluation

# A detailed identification example #1

## Setting (unknown setup)

```
1 G      = tf([1 -2],[.1 .4 1]); G = G/dcgain(G);
2 Ns     = 2^8;
3 fmax   = 5*max(abs(eig(G)))/2/pi;
4 Fs     = 2^(nextpow2(fmax)+1);
5 Ts     = 1/Fs;
```



## Remarks



We do not know  $G$ , but

- ▶ Analyze (visually) the system and ask user if possible
- ▶ Input/output range, type, unit...
- ▶ Evaluate time response  
→ gives an idea of  $f_{max}$   
→  $T_s = \frac{1}{f_s} \approx \frac{1}{5f_{max}}$

# A detailed identification example #1

## Setting (unknown setup)

```
1 % Noise model generator
2 n      = 1e-1; % noise amplitude in percent
3 Gn     = tf(n,[1/100 1]);
```



## Remarks

Noise generator for this numerical test

- ▶ gain  $0.1 \approx 10\%$
- ▶ limited frequency range  $\approx 50/\pi$


But, evaluate

- ▶ sensor noise, bandwidth, range
- ▶ drift, offset...

# A detailed identification example #1

## Signals construction

```
1 % Generate exciting signal
2 FBND      = [0 Fs/4];
3 REV       = false;
4 SHOW      = true;
5 [u1, t1, i1] = insapack.mlbs(Ns, Ts, FBND, REV, SHOW);
```





## MLBS

- ▶ select a frequency range satisfying  $f_{max} < f_s/2$
- ▶ check spectrum and analyse the zero notches

# A detailed identification example #1

## Signals construction

```
1 % Generate exciting signal
2 TYPE      = 'linear';% 'logarithmic';
3 [u2,t2,i2] = insapack.chirp(Ns,Ts,FBND,REV,TYPE,SHOW);
```





### Chirp

- ▶ select a frequency range satisfying  $f_{max} < f_s/2$
- ▶ check spectrum and low energy ranges

# A detailed identification example #1

## Signals construction

```
1 % Generate exciting signal
2 RPHI      = false ;
3 ODD       = 'all' ;
4 [u3,t3,i3] = insapack.mulsine(Ns,Ts,FBND,RPHI,ODD,REV,SHOW);
```







## Multi-sine

- ▶ select a frequency range satisfying  $f_{max} < f_s/2$
- ▶ check spectrum and low energy ranges

# A detailed identification example #1

## Signals construction (application on the system with noise)



# A detailed identification example #1

## Learning vs. validation data

---

```
1 nx      = 3;  
2 u_val   = sig1.u;  
3 t_val   = sig1.t;
```

---

```
1 sig      = sig3;  
2 Ts       = sig.Ts;  
3 t        = sig.t;  
4 u        = sig.u;  
5 y        = sig.y;  
6 yn       = sig.yn;  
7 ytrue    = lsim(G,u_val,t_val);  
8 w        = logspace(-2,log10(1/Ts),200)*2*pi;  
9 Gtrue    = freqresp(G,w);
```

---

### Validation

- ▶ here we use MLBS as validation
- ▶ in practice use more !
- ▶ used metric on accuracy, eigenvalues, ...


### Learning

- ▶ here we use multi-sine
- ▶ can use more than one single
- ▶ can use averaged model
- ▶ can average multiple models...

# A detailed identification example #1

## Time-domain identification with Subspaces Framework

```
1 %%% IDENTIFICATION VIA N4SID
2 Hn4sid = n4sid(u, yn, 1:nx, 'Ts', Ts);
3 Hn4sid = stabsep(ss(Hn4sid));
4 yn4sid = lsim(Hn4sid, u_val, t_val);
5 Gn4sid = freqresp(Hn4sid, w);
```






### N4SID

- ▶ can input a range of dimensions
- ▶ Hankel singular values are here to help selection
- ▶ Here we keep  $n = 3$

# A detailed identification example #1

## Frequency-domain identification in the Loewner Framework

```
1 % Compute FRF
2 [ f , U0 , Y0 , G0 ] = insapack . non_param_freq ( u , yn , Ts ) ;
3 puls = 2 * pi * f ( f < FBND ( end ) / 2 ) ;
4 wRange = 1 : floor ( length ( puls ) / 2 ) * 2 ;
5 puls = 2 * pi * f ( wRange ) ;
6 G0 = G0 ( wRange ) ;
```




### Compute FRF

- ▶ Apply non parametric analysis
- ▶ Estimate the frequency response / sigma (if multiple tests)
- ▶ Pre-treat the frequency data to remove the signals outside the excitation range, filter, ...
- ▶ Post-treat (stability separation)

# A detailed identification example #1

## Frequency-domain identification in the Loewner Framework

```
1 % Loewner
2 [la ,mu,W,V,R,L] = insapack.data2loewner(puls ,G0);
3 opt.target       = nx;
4 [hr ,info]       = insapack.loewner_tng(la ,mu,W,V,R,L ,opt);
5 Hloe            = dss(info.Ar ,info.Br ,info.Cr ,info.Dr ,info.Er);
6 Hloe            = stabsep(Hloe);
7 yloe            = lsim(Hloe ,u_val ,t_val);
8 Gloe            = freqresp(Hloe ,w);
```







### Loewner Framework

- ▶ Construct row and column data
- ▶ Apply Loewner and check Loewner singular decay
- ▶ Select the order
- ▶ Post-treat (stability separation)

# A detailed identification example #1

## Comparison and validation



# Content

Introduction

A detailed identification example #1

**A detailed identification example #2**

Experimental setup


Working methodology

Evaluation

# A detailed identification example #2

## Setting


```
1  rng(1);
2  G      = stabsep(rss(20,1,1)); G = G/dcgain(G);
3  Ns     = 2^9;
4  fmax   = 5*max(abs(eig(G)))/2/pi;
5  Fs     = 2^(nextpow2(fmax)+1);
6  Ts     = 1/Fs;
```



# A detailed identification example #2

## Signals construction


```
1 % Generate exciting signal
2 FBND      = [0 Fs/4];
3 REV       = false;
4 SHOW      = true;
5 [u1, t1, i1] = insapack.mlbs(Ns, Ts, FBND, REV, SHOW);
```



# A detailed identification example #2

## Signals construction


```
1 % Generate exciting signal
2 TYPE      = 'linear';% 'logarithmic';
3 [u2,t2,i2] = insapack.chirp(Ns,Ts,FBND,REV,TYPE,SHOW);
```



# A detailed identification example #2





## Signals construction

```
1 % Generate exciting signal
2 RPHI      = false;
3 ODD       = 'all';
4 [u3, t3, i3] = insapack.mulsine(Ns, Ts, FBND, RPHI, ODD, REV, SHOW);
```



# A detailed identification example #2


## Signals construction



# A detailed identification example #2

## Time-domain identification with Subspaces Framework




```
1 %%% IDENTIFICATION VIA N4SID
2 Hn4sid = n4sid(u,yn,1:nx,'Ts',Ts);
3 Hn4sid = stabsep(ss(Hn4sid));
4 yn4sid = lsim(Hn4sid,u_val,t_val);
5 Gn4sid = freqresp(Hn4sid,w);
```



# A detailed identification example #2

## Frequency-domain identification in the Loewner Framework


```
1 % Compute FRF
2 [f, U0, Y0, G0] = insapack.non_param_freq(u, yn, Ts);
3 puls = 2*pi*f(f < FBND(end)/2);
4 wRange = 1:floor(length(puls)/2)*2;
5 puls = 2*pi*f(wRange);
6 G0 = G0(wRange);
```



# A detailed identification example #2





## Frequency-domain identification in the Loewner Framework

```
1 % Loewner
2 [la ,mu,W,V,R,L] = insapack.data2loewner(puls ,G0);
3 opt.target       = nx;
4 [hr ,info]      = insapack.loewner_tng(la ,mu,W,V,R,L, opt);
5 Hloe           = dss(info.Ar,info.Br,info.Cr,info.Dr,info.Er);
6 Hloe          = stabsep(Hloe);
7 yloe          = lsim(Hloe,u_val,t_val);
8 Gloe          = freqresp(Hloe,w);
```



# A detailed identification example #2

## Comparison and validation



# Content

Introduction

A detailed identification example #1

A detailed identification example #2

**Experimental setup**

Working methodology

Evaluation

# Experimental setup

## The experiments more in details

- ▶ DC motor
- ▶ Flying ping pong ball
- ▶ Small wind tunnel
- ▶ Water tanks
- ▶ Ball on a rail
- ▶ Temperature & flow

# Experimental setup

## The experiments more in details

- ▶ **DC motor**
  - ▶ SISO, stable, linear
- ▶ **Flying ping pong ball**
  - ▶ SIMO, unstable, linear  
sensor potentially nonlinear
- ▶ **Small wind tunnel**
  - ▶ SIMO, stable, linear & delayed  
sensor quite noisy
- ▶ **Water tanks**
  - ▶ SISO, unstable, linear & non-linear  
very slow
- ▶ **Ball on a rail**
  - ▶ SIMO, unstable, linear  
closed-loop identification
- ▶ **Temperature & flow**
  - ▶ MIMO, linear & switched  
possibly 2 identifications, 2 laws

# Experimental setup

## The experiments more in details

- ▶ **DC motor**
  - ▶ **u**: DC voltage / **y**: rotation speed  
objective: tracking, disturbance rejection, digital
- ▶ **Flying ping pong ball**
  - ▶ **u**: DC voltage / **y**: rotation speed & ball height  
objective: stabilization, disturbance rejection
- ▶ **Small wind tunnel**
  - ▶ **u**: DC voltage / **y**: pressure & flow  
objective: tracking, disturbance rejection
- ▶ **Water tanks**
  - ▶ **u**: flow voltage / **y**: water height  
objective: tracking, adaptive
- ▶ **Ball on a rail**
  - ▶ **u**: DC voltage / **y**: beam angle & ball position  
objective: stabilization, disturbance rejection
- ▶ **Temperature & flow**
  - ▶ **u**: voltage / **y**: rotation speed  
objective: tracking, switching (positive system)

# Content

Introduction

A detailed identification example #1

A detailed identification example #2

Experimental setup

**Working methodology**


Evaluation

# Working methodology

## #1 identification and modeling


### Some steps

- ▶ Analyze "visually" the system
- ▶ Ask yourself about its properties
- ▶ Build excitation & validation signals
- ▶ Chose a model structure / complexity
- ▶ Model black/grey/white box model



# Working methodology

## #2 analyze




### Some steps

- ▶ Spectral: poles and zeros for multiple draw
- ▶ Time-domain: impulse, step, MLBS
- ▶ Frequency-domain: Bode gain & phase, Nyquist
- ▶ Parametric sensitivity
- ▶ Analyze realization complexity, parameters
- ▶ Construct a white(grey)-box equivalent model if possible
- ▶ Evaluate which variables are of interest? Gain, phase, delay, oscillation, ...

# Working methodology

## #3 design a control law




### Quelques étapes

- ▶ Define control and performance objectives & constraints (saturation, velocity, bandwidth)
- ▶ Chose actuator & sensors to use (are they reliable?)
- ▶ Chose a control law structure
- ▶ Optimize the parameters of the control (using pole placement, time- or frequency-domain methods, norms...)
- ▶ Is an estimator useful?
- ▶ Analyze stability and robustness margins

# Working methodology

## #4 optimize the setup



### Quelques étapes

- ▶ Filtering can be useful?
- ▶ How it behaves with discretization, sampling, delay, jitter
- ▶ Rounding gains, measurements
- ▶ Imagine sensor loss
- ▶ How to render the system more efficient, less expensive...

# Content

Introduction

A detailed identification example #1

A detailed identification example #2

Experimental setup

Working methodology

**Evaluation**

# Evaluation

## Organization and evaluation

### Organisation

- ▶ Group of 3 persons
- ▶ 5 sessions
  - 2 for identification
  - 1 for analysis
  - 1 for control
  - 1 for improvement & presentation
- ▶ Last session  $\approx 2\text{h}+1\text{h}15$  (all groups)

### Evaluation

- ▶ Presentation
  - 10 minutes (slides & demonstration)
  - 5 minutes (questions)
- ▶ Notation:
  - 10 pts (presentation)
  - 10 pts (participation)
  - Possible different notations according to engagement

# Linear dynamical system identification

... basic elements and Labs guidelines

Charles Pousot-Vassal

February 20, 2026

